

HARVIA SPIRIT

HSP904MXW

The Harvia Spirit electric sauna heater is a high-quality design heater that can be operated with a control unit. The delicate curved form highlights the natural stone surface. The heater's structure guides the steam and heat effectively to make your sauna experience enjoyable and safe.

Advantages

- Stylish and curved design heater
- Plenty of stones visible
- Unique ventilation ducts creating even temperature in the sauna
- Recommended stones: R-991 Round Olivine diabase 5–10 cm x 55 kg
- Small and safe heater mounted on the wall



Features

Main material : Steel

H x W x D : 687.0 x 385.0 x 334.0 mm

Net weight (kg) : 14.0

Installation location : Wall

ID	GTIN	Output (kW)	Sauna room size min - max m3
HSP904MXW	6417659032629	9 kW	8.0-14.0


Related products



SAA00101



R-991



HSP1



HSP3M



SP311



Spare parts

Product	ID	Pcs
Circuit board max. 11 kW 230VAC XE/XW heaters	SP683	1
Heating element 3000W 230V	SPZCU-830	3
Temperature sensor (125C limiter) white	SP248	1
Data cable RJ10 4P4C 5 m RJ10 black	SP311	1
Control panel Harvia Xenio Wifi black	SP694	1
Xenio WIFI remote kit	CX001WIFI	1
Xenio CX110XW IPX5 WiFi black	CX1104XW01	

Technical details

Technical data	Type / attribute	HSP904MXW
	Color	Black
	Power output	9 kW
	Stone sizes	Ø5–10 cm
	Stone amount (kg)	60
Dimensions	Product width	385
	Product height	687
	Product depth (mm)	334
	Net weight (kg)	14
	Gross weight	17
	Package width	420
	Package height	780
	Package depth	375
Safety and installation dimensions	Safety distance front (non-combustible materials)	80
	Safety distance front (combustible materials)	80
	Safety distance right side (combustible materials)	80
	Safety distance right side non-combustible materials	80
	Safety distance left side (combustible materials)	80
	Safety distance left side non-combustible materials	80
	Safety distance side (non-combustible materials)	80
	safety distance to the side wall (combustible materials)	80
	Safety distance behind (non-combustible materials)	80
	Safety distance (Ceiling)	900
	Room min. height(depends on connections and therefore from output, star/delta)	1900
	Installation opening height	1900
	Installation opening width	414
	Installation opening depth	545



Technical images

